#### **Extruded Polystyrene Foam Insulation (XPS)**

### CBIA 2016 Energy Efficiency Forum April 4, 2014

**Presenter:** 

### John Woestman Extruded Polystyrene Foam Association (XPSA)

jwoestman@xpsa.com



### **XPS Insulation**

- R-5 per inch
- Common thickness
  - 1", 1 ½", 2", 3" (and 7/16", ½", ¾")
- Common sizes
  - 2'x8', 4'x8', 4'x9'
  - Square edge (most common), also T&G or shiplap edge
- Common uses
  - Above grade wall, exterior
  - Below grade wall, interior or exterior
  - Under concrete slab



## Design & Construction with Thicker Foam Continuous Insulation - Resources

- Websites
  - XPS manufacturers: Dow, Owens Corning, Pactiv
- Design
  - Dow Builder's Guide
  - Owens Corning Builder's Guide
  - Building Science Corporation
  - Building America
- Fenestration installation
  - XPS mfg. builder guides, and fenestration manufacturer instructions
- Cladding attachment
  - Foam Sheathing Coalition "Tech Matters"



# Dow Building Solutions Test Homes Research Project

Project TEETH
Ten Energy Efficient Test Homes
Midland, Michigan

Multi-home, 5 year research project
Dow Building Solutions partnership with Cobblestone Homes
Designed to meet latest energy code requirements
Determine builder costs to improve efficiency
Investigate performance of several building enclosure designs

All following slides courtesy Dow Building Solutions (Dow Chemical Co.)



### **Project TEETH Research Objectives**

- Demonstrate ways to:
  - Lower the cost of home ownership
  - Improve home performance
- Produce real world data on:
  - Construction cost
    - Building materials purchased by builder through normal channels
  - Energy use
  - Wall durability performance
  - Occupant comfort and perception
- Create output useful in construction decisions



#### **Experimental Design**

#### Three Homes Built For Each Energy Efficiency Design


Baseline HERS 82	Meet 2006 IECC Typical Local Practices (Michigan)
2012 IECC Cavity Insulation Minimum cost HERS 57	Meet 2012 IECC Least Changes & Lowest Possible Price Point
2012 IECC Cavity plus Foam C. I. Premium Package HERS 57	Meet 2012 IECC Continuous Insulation & SPF
Beyond 2012 IECC Premium Package HERS – mid 40s	Beyond 2012 IECC Renewable Ready





#### **Research Neighborhood**

Midland, Michigan Climate Zone 5-6



### **Above Grade Wall and Ceiling Design**

	Cavity	Insulation		ation w/ Foam us Insulation
	2006 IECC	2012 IECC	2012 IECC-CI	Beyond 2012 IECC
Stud Dimensions	2X6 16"o.c.	2X6 16"o.c.	2X4 16"o.c.	2X6 24"o.c.
Stud Cavity	R-19 FG batt	R-19 FG batt	R-16 cc SPF	R-31 cc SPF
Wall Exterior	OSB & Housewrap	OSB & Housewrap	R-5.5 SIS (structural insulating sheathing)	R-5.5 SIS + R-5 XPS
Ceiling	R-38 Dry Blown Cellulose	R-49 Dry Blown Cellulose	R-49 Dry Blown Cellulose	R-12 2"cc SPF & R-49 Dry Blown Cellulose

windows and iviecnanical Design							
	Cavity I	nsulation		ation w/ Foam is Insulation			
	2006 IECC	2012 IECC	2012 IECC-CI	Beyond 2012			

U-.32

**92% AFUE** 

13 SEER

62% Electric

75%

Windows

**Furnace** 

AC

Water Heating

High Efficiency

Lighting

U-.35

80% AFUE

13 SEER

62% Electric

0%

**IECC** 

U-28

**95% AFUE** 

13 SEER

62% Electric

100%

U-.32

**92% AFUE** 

13 SEER

62% Electric

75%

### **Foundation & Floor Design**

	Cavity	Insulation		tion w/ Foam s Insulation
	2006 IECC	2012 IECC	2012 IECC -CI	Beyond 2012 IECC
Under Floor Slab	None	None	None	R-10 XPS
Rim Joist -Interior	R-19 FG batt	R-19 FG batt	R-16 cc SPF	R-16 cc SPF
Rim Joist – Exterior	None	None	R-5 XPS	R-10 XPS
Basement Wall – Interior Finished	R-13 FG batt	R-19 FG batt	R-5 XPS	R-10 XPS
Basement Wall - Interior Unfinished	R-10 FG vinyl faced	R-15 FG vinyl faced	R-5 PIR	R-10 PIR
Basement Wall – Exterior	None	None	R-10 XPS	R-10 XPS

# Construction Cost Comparison Actual Cost Complications

- Lot variations
- > Elevation differences
- Material upgrades
- Weather related costs
- > Price variations
  - ✓ Price fluctuations throughout the term of the project
  - ✓ Different suppliers or subcontractors
- > Invoicing errors
- Quantity variations
  - ✓ Rob Peter to pay Paul
  - ✓ Different subcontractors
  - ✓ Theft
  - ✓ Damage



### **Isolating Energy Related Costs**

- Exclude costs not related to energy levels
- Equalize all material and labor prices across the board
- Equalize or calibrate quantities
  - ✓ Use consistent areas between same house types
  - ✓ Use an actual material count across same house types
    - Make adjustments only when needed based on solid, logical and defensible judgments



### **Cost Summary**

Somerset Model - Ranch	Inst	Framing, sulation & ir Sealing	indows & erior Doors	HVAC	Lię	ghting	TOTAL	Pi	remium from Baseline
2006 IECC	\$	14,888	\$ 3,356	\$ 6,922	\$	-	\$ 25,166		
2012 IECC - Fiber	\$	15,396	\$ 4,545	\$ 6,375	\$	100	\$ 26,416	\$	1,250.27
2012 CI Dow Premium	\$	19,619	\$ 4,545	\$ 6,375	\$	100	\$ 30,639	\$	5,472.96
Beyond 2012 IECC - Renewable Ready	\$	27,142	\$ 5,477	\$ 7,675	\$	350	\$ 40,644	\$	15,478.09
Kendall Model - 2 story 2006 IECC	\$	16,886	\$ 3,660	\$ 6,922	\$	-	\$ 27,467		
2012 IECC - Fiber	\$	17,215	\$ 4,928	\$ 6,775	\$	100	\$ 29,018	\$	1,550.24
2012 CI Dow Premium	\$	21,086	\$ 4,928	\$ 6,775	\$	100	\$ 32,889	\$	5,421.55
Beyond 2012 IECC - Renewable Ready	\$	28,789	\$ 5,828	\$ 8,075	\$	350	\$ 43,042	\$	15,574.57
Preston Model - Ranch									
2006 IECC	\$	16,945	\$ 3,447	\$ 6,922	\$	-	\$ 27,314		
2012 IECC - Fiber	\$	17,744	\$ 5,130	\$ 6,375	\$	100	\$ 29,350	\$	2,035.68
2012 CI Dow Premium	\$	22,297	\$ 5,130	\$ 6,375	\$	100	\$ 33,902	\$	6,588.09

29,023 \$

6,146 \$

7,675 \$ 350 \$ 43,194 \$

Beyond 2012 IECC - Renewable Ready

### **Cost Summary**

Somerset Model - Ranch	Ins	Framing, sulation & ir Sealing	indows & erior Doors	HVAC	Lię	ghting	TOTAL	Pre	emium from Baseline
2006 IECC	\$	14,888	\$ 3,356	\$ 6,922	\$	-	\$ 25,166		
2012 IECC - Fiber	\$	15,396	\$ 4,545	\$ 6,375	\$	100	\$ 26,416	\$	1,250.27
2012 CI Dow Premium	\$	19,619	\$ 4,545	\$ 6,375	\$	100	\$ 30,639	\$	5,472.96
Beyond 2012 IECC - Renewable Ready	\$	27,142	\$ 5,477	\$ 7,675	\$	350	\$ 40,644	\$	15,478.09
Kendall Model - 2 story 2006 IECC	\$	16,886	\$ 3,660	\$ 6,922	\$	-	\$ 27,467		
2012 IECC - Fiber	\$	17,215	\$ 4,928	\$ 6,775	\$	100	\$ 29,018		1,550.24
2012 CI Dow Premium	\$	21,086	\$ 4,928	\$ 6,775	\$	100	\$ 32,889	\$	5,421.55
Beyond 2012 IECC - Renewable Ready	\$	28,789	\$ 5,828	\$ 8,075	\$	350	\$ 43,042	\$	15,574.57
Preston Model - Ranch									
2006 IECC	\$	16,945	\$ 3,447	\$ 6,922	\$	-	\$ 27,314		
2012 IECC - Fiber	\$	17,744	\$ 5,130	\$ 6,375	\$	100	\$ 29,350		2,035.68
2012 CI Dow Premium	\$	22,297	\$ 5,130	\$ 6,375	\$	100	\$ 33,902	\$	0,300.09

29,023 \$

6,146 \$


7,675 \$ 350 \$ 43,194 \$


Beyond 2012 IECC - Renewable Ready

# Hygrothermal Instrumentation & Data Acquisition

- ☐ Moisture Content, Temperature, RH
- ☐ Inside wall areas in each house
- Multiple measurements each measurement area
- ☐ Exterior temperature, RH













## **Hygrothermal Performance Above Grade Wall**

Sheathing Moisture Content Mid-height of Wall




## Hygrothermal Performance Above Grade Wall






# Energy Target vs. Confirmed HERS Index





### **Comparison of Air Leakage**

#### Air Changes/hour at 50 Pascals





## 2012 IECC Without & With Continuous Insulation




**OSB Plus Housewrap** 



**R-5 Continuous Insulation** 


## **Energy Actual vs. Modeled Heating – Winter 2012-2013**

#### Total kBTU 10/2012 - 5/2013 per Build type



## **Energy Actual vs. Modeled Cooling – Summer 2013**

Average Cooling kBTU 5/2013 - 9/2013 per Build type (Occupied Homes Only)



■ Actual ■ Modeled



## Occupant Survey: General Observations

#### Notes:

- Two surveys have been conducted to date
- Occupants do not know the energy performance strategy of their home
- Nearly all say it is important to reduce the energy use in their homes
- They closely follow their energy bills
- They don't have a good understanding on the impact they have on the amount of energy they use
- > Some associate higher than expected energy bills to poor construction quality



How efficiently is the home performing energy-wise?

2006 IECC	2012 IECC - Cavity	2012 IECC – Cavity + Foam	Beyond 2012
Less than pleased		Neutral	



How satisfied are you with the level of warmth in your home when it is cold outside?

2006 IECC	2012 IECC – Cavity	2012 IECC – Cavity + Foam	Beyond 2012
		Pleased	



How satisfied are you with the level of cooling in your home when it is hot outside?

2006 IECC	2012 IECC – Cavity	2012 IECC – Cavity + Foam	Beyond 2012



Does the temperature feel the same to you throughout all the rooms of your home?

2006 IECC	2012 IECC - Cavity	2012 IECC – Cavity + Foam	Beyond 2012



Does your home feel drafty?

2006 IECC	2012 IECC – Cavity	2012 IECC – Cavity + Foam	Beyond 2012



### **Next Steps**

- Report Winter 2013-14 in May
- Compare % of H&C to total energy used
- Compare reported T-stat set point to actual temperature
- Focus group
  - > \$ Comfort
  - > \$ Durability
  - Share Actual Data



### **Summary & Conclusions**

- Cost to build to 2012 IECC was lower than many estimates
- Foam strategies resulted in significant improvements in air leakage
- Actual energy used to heat was lower than model for three out of four strategies
- Exterior insulation above and below grade produced warmer and dryer assemblies
- ➤ Consumers are in need of better information on the energy efficiency features of their homes and the role they play in energy usage

